

Project _____

Date _____

Catalog # _____

Type and style of customers fixture _____

Comments _____



11213 N Garnett Road
Owasso, OK 74055
Tel: (918) 504-6595
Fax: (918) 553-6444

ICON SERIES LED ACORN RETROFIT LUMINAIRES

CONSTRUCTION

Up to eight high efficiency LED arrays mounted to proprietary unitary heat sink. Heat sink and power supplies are bolted to adapter plates.

MOUNTING

The adapter plates are fastened to the existing fixture. Available in 2000K, 2200K, 2500K, 2750K, 3000K, 3500K, 4000K and 5000K

ELECTRICAL

120 to 277VAC input with full dimming capability. 480VAC version is available. Standard three pin TE style connectors are provided for quick and simple installation. Additional plugs to match manufacturer's fixtures as well as 3 wire pigtails are available.

RELIABILITY

Patented, proven and reliable technology (US Patent number: 9,964,288). Case studies are available upon request.

WARRANTY

Standard five-year warranty on all retrofit luminaires. Terms and conditions apply.



CATALOG NUMBERS

80 WATT RETROFIT LUMINAIRES

5100-ACRN-80-4T-5000,	120 to 277VAC 80 watt, 4 element LED for prismatic globes
5100-ACRN-80-4T-4000,	120 to 277VAC 80 watt, 4 element LED for prismatic globes
5100-ACRN-80-4T-3500,	120 to 277VAC 80 watt, 4 element LED for prismatic globes
5100-ACRN-80-4T-3000,	120 to 277VAC 80 watt, 4 element LED for prismatic globes
5100-ACRN-80-4T-2700,	120 to 277VAC 80 watt, 4 element LED for prismatic globes
5100-ACRN-80-4T-2500,	120 to 277VAC 80 watt, 4 element LED for prismatic globes
5100-ACRN-80-4T-2200,	120 to 277VAC 80 watt, 4 element LED for prismatic globes
5100-ACRN-80-4T-2000,	120 to 277VAC 80 watt, 4 element LED for prismatic globes
5100-ACRN-80-8T-5000,	120 to 277VAC 80 watt, 8 element LED for transparent globes
5100-ACRN-80-8T-4000,	120 to 277VAC 80 watt, 8 element LED for transparent globes
5100-ACRN-80-8T-3500,	120 to 277VAC 80 watt, 8 element LED for transparent globes
5100-ACRN-80-8T-3000,	120 to 277VAC 80 watt, 8 element LED for transparent globes
5100-ACRN-80-8T-2700,	120 to 277VAC 80 watt, 8 element LED for transparent globes
5100-ACRN-80-8T-2500,	120 to 277VAC 80 watt, 8 element LED for transparent globes
5100-ACRN-80-8T-2200,	120 to 277VAC 80 watt, 8 element LED for transparent globes
5100-ACRN-80-8T-2000,	120 to 277VAC 80 watt, 8 element LED for transparent globes

40 WATT RETROFIT LUMINAIRES

5100-ACRN-40-4T-5000,	120 to 277VAC 40 watt, 4 element LED for prismatic globes
5100-ACRN-40-4T-4000,	120 to 277VAC 40 watt, 4 element LED for prismatic globes
5100-ACRN-40-4T-3500,	120 to 277VAC 40 watt, 4 element LED for prismatic globes
5100-ACRN-40-4T-3000,	120 to 277VAC 40 watt, 4 element LED for prismatic globes
5100-ACRN-40-4T-2700,	120 to 277VAC 40 watt, 4 element LED for prismatic globes
5100-ACRN-40-4T-2500,	120 to 277VAC 40 watt, 4 element LED for prismatic globes
5100-ACRN-40-4T-2200,	120 to 277VAC 40 watt, 4 element LED for prismatic globes
5100-ACRN-40-4T-2000,	120 to 277VAC 40 watt, 4 element LED for prismatic globes
5100-ACRN-40-8T-5000,	120 to 277VAC 40 watt, 8 element LED for transparent globes
5100-ACRN-40-8T-4000,	120 to 277VAC 40 watt, 8 element LED for transparent globes
5100-ACRN-40-8T-3500,	120 to 277VAC 40 watt, 8 element LED for transparent globes
5100-ACRN-40-8T-3000,	120 to 277VAC 40 watt, 8 element LED for transparent globes
5100-ACRN-40-8T-2700,	120 to 277VAC 40 watt, 8 element LED for transparent globes
5100-ACRN-40-8T-2500,	120 to 277VAC 40 watt, 8 element LED for transparent globes
5100-ACRN-40-8T-2200,	120 to 277VAC 40 watt, 8 element LED for transparent globes
5100-ACRN-40-8T-2000,	120 to 277VAC 40 watt, 8 element LED for transparent globes