



11213 N Garnett Road  
Owasso, OK 74055  
Tel: (918) 504-6595  
Fax: (918) 553-6444

Project _____
Date _____
Catalog # _____
Type and style of customers fixture _____
Comments _____
_____
_____

# ASTROPHILE SERIES NARROW BAND AMBER AMBER FIXTURES

## CONSTRUCTION

Up to 60 high efficiency LED arrays mounted to proprietary unitary heat sinks. Heat sinks and power supplies are bolted to interchangeable adapter plates.

## MOUNTING

The Astrophile street light fixtures are designed to be mounted to 2.40" tenons.

## OPTICS

The Astrophile street light fixtures is available in type I, II, III, IV, V.

## PEAK DOMINANT WAVELENGTH

Available in 592nm, 592nm, and 595nm  $\pm$ 2.5nm

## ELECTRICAL

120 to 277VAC input with full dimming capability. 480VAC version is available. Standard three terminal screw type terminal block are provided for quick and simple installation. A 3 wire pigtail is also available.

## RELIABILITY

Patented, proven and reliable technology (US Patent number: 9,964,288). Case studies are available upon request.



## **WARRANTY**

Standard five-year warranty on all retrofit luminaires. Terms and conditions apply.

## **CATALOG NUMBERS**

### **100 WATT STREET LIGHT FIXTURES**

4000-PS1828-100-589,	120 to 277VAC 100 watt, 60 element LED
4000-PS1828-100-592,	120 to 277VAC 100 watt, 60 element LED
4000-PS1828-100-595,	120 to 277VAC 100 watt, 60 element LED

### **70 WATT STREET LIGHT FIXTURES**

4000-PS1828-70-589,	120 to 277VAC 70 watt, 48 element LED
4000-PS1828-70-592,	120 to 277VAC 70 watt, 48 element LED
4000-PS1828-70-559,	120 to 277VAC 70 watt, 48 element LED

### **45 WATT STREET LIGHT FIXTURES**

4000-PS1828-45-589,	120 to 277VAC 45 watt, 48 element LED
4000-PS1828-45-592,	120 to 277VAC 45 watt, 48 element LED
4000-PS1828-45-595,	120 to 277VAC 45 watt, 48 element LED