

Project \_\_\_\_\_

Date \_\_\_\_\_

Catalog # \_\_\_\_\_

Type and style of customers fixture \_\_\_\_\_

Comments \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_



11213 N Garnett Road  
Owasso, OK 74055  
Tel: (918) 504-6595  
Fax: (918) 553-6444

# ASTROPHILE SERIES PHOSPHOR CONVERTED AMBER FIXTURES

## CONSTRUCTION

Up to 4 high efficiency LED arrays mounted to proprietary unitary heat sinks. Heat sinks and power supplies are bolted to interchangeable adapter plates.

## MOUNTING

The Astrophile street light fixtures are designed to be mounted to 2.40" tenons.

## OPTICS

The Astrophile street light fixtures is available in type I, II, III, IV, V.

## COLOR TEMPERATURE

Available in 2000K and 2200K

## ELECTRICAL

120 to 277VAC input with full dimming capability. 480VAC version is available. Standard three terminal screw type terminal block are provided for quick and simple installation. A 3 wire pigtail is also available.

## RELIABILITY

Patented, proven and reliable technology (US Patent number: 9,964,288). Case studies are available upon request.



## **WARRANTY**

Standard five-year warranty on all retrofit luminaires. Terms and conditions apply.

## **CATALOG NUMBERS**

### **120 AND 160 WATT STREET LIGHT FIXTURES**

4000-1JN17-160-2000, 120 to 277VAC 160 watt, 4 element LED

4000-1JN17-120-2000, 120 to 277VAC 120 watt, 4 element LED

4000-1JN17-160-2200, 120 to 277VAC 160 watt, 4 element LED

4000-1JN17-160-2200, 120 to 277VAC 120 watt, 4 element LED

### **45 AND 90 WATT STREET LIGHT FIXTURES**

4000-EPH58-90-2000, 120 to 277VAC 90 watt, 2 element LED

4000-EPH58-90-2200, 120 to 277VAC 90 watt, 2 element LED

4000-EPH58-45-2000, 120 to 277VAC 45 watt, 2 element LED

4000-EPH58-45-2200, 120 to 277VAC 45 watt, 2 element LED