

Project _____

Date _____

Catalog # _____

Type and style of customers fixture _____

Comments



11213 N Garnett Road
Owasso, OK 74055
Tel: (918) 504-6595
Fax: (918) 553-6444

PRESTIGE SERIES LED RETROFIT LUMINAIRES

CONSTRUCTION

Up to 4 high efficiency LED arrays mounted to proprietary unitary heat sinks. Heat sinks and power supplies are bolted to adapter plates.

MOUNTING

The PRESTIGE retrofit luminaires mount to the existing fixtures bolt pattern. The adapter plates are designed to accommodate all to known decorative and bell-shaped fixtures.

OPTICS

The PRESTIGE retrofit luminaire is designed to provide the exact distribution pattern of the existing fixture. Additional distribution patterns are available.

COLOR TEMPERATURE

Available in 2000K, 2200K, 2500K, 2750K, 3000K, 3500K, 4000K and 5000K

ELECTRICAL

120 to 277VAC input with full dimming capability. 480VAC version is available. Standard three pin TE style connectors are provided for quick and simple installation. Additional plugs to match manufacturers fixtures as well as 3 wire pigtailed are available.



RELIABILITY

Patented, proven and reliable technology (US Patent number: 9,964,288). Case studies are available upon request.

WARRANTY

Standard five-year warranty on all retrofit luminaires. Terms and conditions apply.

CATALOG NUMBERS

90 AND 120 WATT RETROFIT LUMINAIRES

5100-DL120-5000,	120 to 277VAC 120 watt, 4 element LED
5100-DL120-4000,	120 to 277VAC 120 watt, 4 element LED
5100-DL120-3500,	120 to 277VAC 120 watt, 4 element LED
5100-DL120-3000,	120 to 277VAC 120 watt, 4 element LED
5100-DL120-2700,	120 to 277VAC 120 watt, 4 element LED
5100-DL120-2500,	120 to 277VAC 120 watt, 4 element LED
5100-DL120-2200,	120 to 277VAC 120 watt, 4 element LED
5100-DL120-2000,	120 to 277VAC 120 watt, 4 element LED
5100-DL90-5000,	120 to 277VAC 90 watt, 3 element LED
5100-DL90-4000,	120 to 277VAC 90 watt, 3 element LED
5100-DL90-3500,	120 to 277VAC 90 watt, 3 element LED
5100-DL90-3000,	120 to 277VAC 90 watt, 3 element LED
5100-DL90-2700,	120 to 277VAC 90 watt, 3 element LED
5100-DL90-2500,	120 to 277VAC 90 watt, 3 element LED
5100-DL90-2200,	120 to 277VAC 90 watt, 3 element LED
5100-DL90-2000,	120 to 277VAC 90 watt, 3 element LED

40 AND 60 WATT RETROFIT LUMINAIRES

5100-DL60-5000,	120 to 277VAC 60 watt, 2 element LED
5100-DL60-4000,	120 to 277VAC 60 watt, 2 element LED
5100-DL60-3500,	120 to 277VAC 60 watt, 2 element LED
5100-DL60-3000,	120 to 277VAC 60 watt, 2 element LED
5100-DL60-2700,	120 to 277VAC 60 watt, 2 element LED
5100-DL60-2500,	120 to 277VAC 60 watt, 2 element LED
5100-DL60-2200,	120 to 277VAC 60 watt, 2 element LED
5100-DL60-2000,	120 to 277VAC 60 watt, 2 element LED
5100-DL40-5000,	120 to 277VAC 40 watt, 1 element LED
5100-DL40-4000,	120 to 277VAC 40 watt, 1 element LED
5100-DL40-3500,	120 to 277VAC 40 watt, 1 element LED
5100-DL40-3000,	120 to 277VAC 40 watt, 1 element LED
5100-DL40-2700,	120 to 277VAC 40 watt, 1 element LED
5100-DL40-2500,	120 to 277VAC 40 watt, 1 element LED
5100-DL40-2200,	120 to 277VAC 40 watt, 1 element LED
5100-DL40-2000,	120 to 277VAC 40 watt, 1 element LED